

LEO Energy NiMH battery exhibits superb efficiency and durability for both high temperature and low temperature operations, at the range from -10°C to 70°C.



Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimension With Tube		Standard Charge		Rapid Charge		Weight Approx (g)
			Diameter (mm)	Height (mm)	Current (mA)	Time (h)	Current (mA)	Time (h)	
1/4AAA80	1.2	80	10.5	10	8	15	80	1.2	5
1/3AAA120	1.2	120	10.5	15.0	12	15	120	1.2	6
2/3AAA300	1.2	300	10.5	29.0	28	15	300	1.2	8
AAA600	1.2	600	10.5	44.5	60	15	600	1.2	12
AAA700	1.2	700	10.5	44.5	70	15	700	1.2	13
AAA800	1.2	800	10.5	44.5	80	15	800	1.2	13
AAA850	1.2	850	10.5	44.5	85	15	850	1.2	13
5/4AAA700	1.2	700	10.5	50.5	70	15	700	1.2	13
5/4AAA800	1.2	800	10.5	50.5	80	15	800	1.2	14
5/3AAA900	1.2	900	10.5	66.5	90	15	900	1.2	18
5/3AAA1000	1.2	1000	10.5	66.5	100	15	1000	1.2	18
N350	1.2	350	12.0	30.0	35	15	350	1.2	10
1/3N150	1.2	150	12.0	16.5	15	15	150	1.2	6
1/2AA600	1.2	600	14.5	24.0	60	15	600	1.2	13
2/3AA700	1.2	700	14.5	29.0	70	15	700	1.2	14
4/5AA1200	1.2	1200	14.5	43.0	120	15	1200	1.2	23
AA1200	1.2	1200	14.5	50.5	120	15	1200	1.2	25
AA1300	1.2	1300	14.5	50.5	130	15	1300	1.2	26
AA1500	1.2	1500	14.5	50.5	150	15	1500	1.2	28
AA1600	1.2	1600	14.5	50.5	160	15	1600	1.2	28
AA1800	1.2	1800	14.5	50.5	180	15	1800	1.2	29
AA2000	1.2	2000	14.5	50.5	200	15	2000	1.2	29
AA2100	1.2	2100	14.5	50.5	210	15	2100	1.2	30
AA2200	1.2	2200	14.5	50.5	220	15	2200	1.2	30
AA2300	1.2	2300	14.5	50.5	230	15	2300	1.2	31
AA2400	1.2	2400	14.5	50.5	240	15	2400	1.2	31

Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimension With Tube		Standard Charge		Rapid Charge		Weight Approx (g)
			Diameter (mm)	Height (mm)	Current (mA)	Time (h)	Current (mA)	Time (h)	
4/3AA2200	1.2	2200	14.5	67.0	220	15	2200	1.2	33
2/3A1100	1.2	1100	17.0	28.0	110	15	1100	1.2	21
4/5A1900	1.2	1900	17.0	43.0	190	15	1900	1.2	33
A2100	1.2	2100	17.0	50.0	210	15	2100	1.2	36
A2300	1.2	2300	17.0	50.0	230	15	2300	1.2	38
4/3A3600	1.2	3600	17.0	67.0	360	15	3600	1.2	47
4/3A3800	1.2	3800	17.0	67.0	380	15	3800	1.2	48
4/5SC2200	1.2	2200	23.0	34.0	220	15	2200	1.2	46
SC2500	1.2	2500	23.0	43.0	250	15	2500	1.2	58
SC2800	1.2	2800	23.0	43.0	280	15	2800	1.2	59
SC3000	1.2	3000	23.0	43.0	300	15	3000	1.2	60
SC3300	1.2	3300	23.0	43.0	330	15	3300	1.2	62
C1500	1.2	1500	25.8	51.0	150	15	1500	1.2	42
C1800	1.2	1800	25.8	51.0	180	15	1800	1.2	42
C4000	1.2	4000	25.8	51.0	400	15	4000	1.2	77
C4500	1.2	4500	25.8	51.0	450	15	4500	1.2	77
D1800	1.2	1800	33.0	61.8	180	15	1800	1.2	76
D2200	1.2	2200	33.0	61.8	220	15	2200	1.2	76
D7000	1.2	7000	33.0	61.8	700	15	7000	1.2	165
D8000	1.2	8000	33.0	61.8	800	15	8000	1.2	170
D9000	1.2	9000	33.0	61.8	900	15	9000	1.2	175
F12000	1.2	12000	33.0	90.5	1200	15	12000	1.2	210
F13000	1.2	13000	33.0	90.5	1300	15	13000	1.2	220
F14000	1.2	14000	33.0	90.5	1400	15	14000	1.2	230