

LIMNO₂ CYLINDRICAL BATTERY



Model		(V)	(mAh)	Dimension		Operating Current (max.mA)		Cut off (V)	Weight Approx (g)	Operating Temp (°C)
GB	IEC			Dia. (mm)	Height (mm)	Cont	Pulse			
CR11108	1/3N	3.0	160	11.6	10.8	5	80	2.0	3	-40~+60
CR14250	1/2AA	3.0	600	14.5	25.0	100	400	2.0	9	-40~+60
CR14335	2/3AA	3.0	800	14.5	33.5	100	400	2.0	13	-40~+60
CR14505	AA	3.0	1000	14.5	50.5	100	400	2.0	15	-40~+60
CR15270	CR2	3.0	750	15.0	27.0	100	400	2.0	15	-40~+60
CR17250		3.0	700	17.0	25.0	100	400	2.0	12	-40~+60
CR17335	CR123A	3.0	1300	17.0	33.5	500	1500	2.0	17	-40~+60
2CR17335	2CR5	6.0	1300	34L X 17W	45	500	1000	4.0	35	-40~+60
2CR17335	CR-P2	6.0	1300	34.8L X 19.5W	35.8	500	1000	4.0	35	-40~+60
CR17450		3.0	2200	17.0	45.0	500	1000	2.0	25	-40~+60
CR20590		3.0	2000	20.2	59.0	400	1000	2.0	42	-40~+60
CR25187		3.0	900	25.0	18.7	200	400	2.0	22	-40~+60
CR26500	C	3.0	4500	26.2	50.0	500	1000	2.0	55	-40~+60
CR34615	D	3.0	8000	34.2	61.5	500	2000	2.0	110	-40~+60
CR-V3		3.0	3000	28.5L X 14.5W	51.8	200	800	2.0	38	-40~+60

LI/MNO₂ BUTTON CELLS BATTERY



Model	(V)	(mAh)	Dimension		Operating Current (max.mA)		Cut off (V)	Weight Approx (g)	Operating Temp (°C)
IEC			Dia (mm)	Height (mm)	Cont	Pulse			
CR1130	3.0	50	11.6	3.0	1.5	3	2.0	1.1	-30~+60
CR1220	3.0	35	12.5	2.0	1.5	5	2.0	0.9	-30~+60
CR2430	3.0	270	24.5	3.0	1.8	15	2.0	4.2	-30~+60
CR1620	3.0	60	16.0	2.0	1.5	8	2.0	1.3	-30~+60
CR2016	3.0	70	20.0	1.6	1.8	8	2.0	1.7	-30~+60
CR2025	3.0	140	20.0	2.5	1.8	12	2.0	2.5	-30~+60
CR2032	3.0	210	20.0	3.2	1.8	12	2.0	3.1	-30~+60
CR2450	3.0	550	24.5	5.0	1.8	15	2.0	6.2	-30~+60



LI-SOCL₂ CYLINDRICAL BATTERY



Model		(V)	(mAh)	Dimension		Operating Current (max.mA)		Cutoff (V)	Weight Approx. (g)	Operating Temp (°C)
GB	IEC			Dia. (mm)	Height (mm)	Cont	Pulse			
ER12130		3.6	70	12.0	13.0	2	5	2.0	5	-45~+85
ER13170		3.6	450	13.5	17.0	5	25	2.0	5	-45~+85
ER14250	1/2AA	3.6	1300	14.5	25.0	10	100	2.0	10	-45~+85
ER14335	2/3AA	3.6	1450	14.5	33.5	10	100	2.0	13	-45~+85
ER14505	AA	3.6	2400	14.5	50.5	20	100	2.0	20	-45~+85
ER17335		3.6	1500	17.0	33.5	20	100	2.0	20	-45~+85
ER17450		3.6	1900	17.0	45.0	50	200	2.0	25	-45~+85
ER18505	A	3.6	3200	18.8	50.5	50	200	2.0	30	-45~+85
ER26500	C	3.6	8500	26.2	50.0	100	200	2.0	54	-45~+85
ER34320	1/2D	3.6	5000	34.2	32.0	120	300	2.0	54	-45~+85
ER34615	D	3.6	16000	34.0	61.5	200	500	2.0	100	-45~+85
ER14250M	1/2AA	3.6	800	14.5	25.0	100	400	2.0	10	-45~+85
ER14505M	AA	3.6	1800	14.5	50.5	300	600	2.0	20	-45~+85
ER26500M	C	3.6	6500	26.2	50.0	1000	1500	2.0	54	-45~+85
ER34615M	D	3.6	12000	34.0	61.5	2000	4000	2.0	100	-45~+85